SLIDE SWITCHES

CL-SB

RoHS compliant



INTERNAL STRUCTURE



Part name	Material	Flammability
① Cover	Stainless steel (SUS 304)	—
② Slider	Polyamido	UL94V-0
③ Housing	Polyphenylenesulphide	UL94V-0
④ Moving contact	Copper alloy, gold or silver plate	—
⑤ Fixed contact	Copper alloy, gold or silver plate	—
⑥ Terminal pin	Copper alloy, gold or silver plate	—

FEATURES

- Wide variety
  (circuit composition, operating direction, terminal shape: J-hook, Gull wing, Through hole pins)
- Standardization of the silver contacts as well as gold contacts
- Stroke is 2mm
- Using heat-resistant resin to support reflow soldering mounting
- Adopted Twin-contacts mechanism

PART NUMBER DESIGNATION

CL - SB - 2 3 B - 0 2 T

Series name

No. of poles
1 : 1 pole
2 : 2 poles

No. of positions
2 : 2 positions
3 : 3 positions

Shape of terminal
A : J-hook
B : Gull wing
C : Through hole pins

Setting position
0 : Top setting
1 : Side setting

Contact material
1 : Silver
2 : Gold

Form of packaging
T : Taping
Blank : Bulk in plastic bag

※Please refer to the LIST OF PART NUMBERS when placing orders.

CL-SB
SLIDE SWITCHES

■LIST OF PART NUMBERS

Setting position	No. of poles	No. of positions	Contact material		Soldering method	Form of packaging	Pieces in package
			Silver	Gold			
Top setting	1	2	CL-SB-12A-01T	CL-SB-12A-02T	Reflow	Taping	500pcs. / reel
			CL-SB-12A-01	CL-SB-12A-02		Plastic bag	50pcs. / pack
			CL-SB-12B-01T	CL-SB-12B-02T		Taping	500pcs. / reel
			CL-SB-12B-01	CL-SB-12B-02		Plastic bag	50pcs. / pack
			CL-SB-12C-01	CL-SB-12C-02	Manual, Dip	Plastic bag	50pcs. / pack
		3	CL-SB-13A-01T	CL-SB-13A-02T	Reflow	Taping	500pcs. / reel
			CL-SB-13A-01	CL-SB-13A-02		Plastic bag	50pcs. / pack
			CL-SB-13B-01T	CL-SB-13B-02T		Taping	500pcs. / reel
			CL-SB-13B-01	CL-SB-13B-02		Plastic bag	50pcs. / pack
			CL-SB-13C-01	CL-SB-13C-02	Manual, Dip	Plastic bag	50pcs. / pack
	2	2	CL-SB-22A-01T	CL-SB-22A-02T	Reflow	Taping	500pcs. / reel
			CL-SB-22A-01	CL-SB-22A-02		Plastic bag	50pcs. / pack
			CL-SB-22B-01T	CL-SB-22B-02T		Taping	500pcs. / reel
			CL-SB-22B-01	CL-SB-22B-02		Plastic bag	50pcs. / pack
			CL-SB-22C-01	CL-SB-22C-02	Manual, Dip	Plastic bag	50pcs. / pack
		3	CL-SB-23A-01T	CL-SB-23A-02T	Reflow	Taping	500pcs. / reel
			CL-SB-23A-01	CL-SB-23A-02		Plastic bag	50pcs. / pack
			CL-SB-23B-01T	CL-SB-23B-02T		Taping	500pcs. / reel
			CL-SB-23B-01	CL-SB-23B-02		Plastic bag	50pcs. / pack
			CL-SB-23C-01	CL-SB-23C-02	Manual, Dip	Plastic bag	50pcs. / pack
Side Setting	1	2	CL-SB-12A-11T	CL-SB-12A-12T	Reflow	Taping	500pcs. / reel
			CL-SB-12A-11	CL-SB-12A-12		Plastic bag	50pcs. / pack
			CL-SB-12B-11T	CL-SB-12B-12T		Taping	500pcs. / reel
			CL-SB-12B-11	CL-SB-12B-12		Plastic bag	50pcs. / pack
			CL-SB-12C-11	CL-SB-12C-12	Manual, Dip	Plastic bag	50pcs. / pack
		3	CL-SB-13A-11T	CL-SB-13A-12T	Reflow	Taping	500pcs. / reel
			CL-SB-13A-11	CL-SB-13A-12		Plastic bag	50pcs. / pack
			CL-SB-13B-11T	CL-SB-13B-12T		Taping	500pcs. / reel
			CL-SB-13B-11	CL-SB-13B-12		Plastic bag	50pcs. / pack
			CL-SB-13C-11	CL-SB-13C-12	Manual, Dip	Plastic bag	50pcs. / pack
	2	2	CL-SB-22A-11T	CL-SB-22A-12T	Reflow	Taping	500pcs. / reel
			CL-SB-22A-11	CL-SB-22A-12		Plastic bag	50pcs. / pack
			CL-SB-22B-11T	CL-SB-22B-12T		Taping	500pcs. / reel
			CL-SB-22B-11	CL-SB-22B-12		Plastic bag	50pcs. / pack
			CL-SB-22C-11	CL-SB-22C-12	Manual, Dip	Plastic bag	50pcs. / pack
		3	CL-SB-23A-11T	CL-SB-23A-12T	Reflow	Taping	500pcs. / reel
			CL-SB-23A-11	CL-SB-23A-12		Plastic bag	50pcs. / pack
			CL-SB-23B-11T	CL-SB-23B-12T		Taping	500pcs. / reel
			CL-SB-23B-11	CL-SB-23B-12		Plastic bag	50pcs. / pack
			CL-SB-23C-11	CL-SB-23C-12	Manual, Dip	Plastic bag	50pcs. / pack

※Verify the above part numbers when placing orders.
Taping version can be supplied only in reel unit.

CL-SB
SLIDE SWITCHES

■ STANDARD SPECIFICATIONS

Operating temperature range	−40 ~ 85 °C
Storage temperature range	
Sealing	Non Washable
Net weight	0.21 g (CL-SB-12*-0*) 0.21 g (CL-SB-12*-1*) 0.22 g (CL-SB-22*-0*) 0.22 g (CL-SB-22*-1*) 0.26 g (CL-SB-13*-0*) 0.26 g (CL-SB-13*-1*) 0.28 g (CL-SB-23*-0*) 0.28 g (CL-SB-23*-1*)

■ MECHANICAL CHARACTERISTICS

No. of positions	2, 3	
Stroke	2 mm	
Operation force	2 Contacts (CL-SB-*2*-**)	A ⇔ B ※1 1.5 ± 1.0 N {0.153 ± 0.102kgf}
	3 Contacts (CL-SB-*3*-**)	A → B / C → B ※2 1.5 ± 1.0 N {0.153 ± 0.102kgf} B → A / B → C 2.5 ± 1.5 N {0.255 ± 0.153kgf}
Stop strength	20 N {2.04 kgf} 15 s	
Solderability	245 ± 3 °C, 2 ~ 3 s	
Soldering heat	Flow : 260 ± 3 °C, 5 ~ 6 s Reflow : 255 °C (Peak temperature) (Please refer to the profile below)	
	Manual soldering : 380 ± 10 °C, 3 ~ 4 s	
Shear	5 N {0.51 kgf} 10 s	
Substrate bending	Width 90 mm, bend 3 mm, 5 s, 1 time	
Pull-off strength	5 N {0.51 kgf} 10s	

{ } : Reference only

※1



※2



■ ELECTRICAL CHARACTERISTICS

Contact rating Non-switching Switching Minimum	DC50 V 200 mA DC12 V 200 mA DC20 mV 1 μA (Gold contacts) DC5 V 10 mA (Silver contacts)	
Contact timing	Non-shorting	
Contact resistance	70mΩ maximum (Gold contacts) 50mΩ maximum (Silver contacts)	1.5 mA 1 kHz 20 mV maximum
Insulation resistance	100 MΩ minimum (DC500 V)	
Dielectric strength	AC500 V, 60 s	

■ ENVIRONMENTAL CHARACTERISTICS

Vibration	Amplitude 1.5 mm or Acceleration 98 m/s^2, 10-500-10 Hz, 3 directions for 2 h each
Shock	490 m/s^2, 11 ms 6 directions for 3 times each
Load life	10000 cycles DC12 ± 0.5V, 200 ± 10mA
Humidity	40 °C, Relative humidity 90 ~ 95 %, 240 h
High temperature exposure	85 °C, 96 h
Low temperature exposure	−40 °C, 96 h
Thermal shock	−40 (0.5 h) ~ 85 °C (0.5 h), 5 cycles

〈Reflow profile for soldering heat evaluation〉



Reflow : two times maximum

CL-SB
SLIDE SWITCHES

OUTLINE DIMESIONS

Unless otherwise specified, tolerance: ± 0.3 (Unit: mm)

● CL-SB-12A-01
● CL-SB-12A-02



● CL-SB-12B-01
● CL-SB-12B-02



● CL-SB-12C-01
● CL-SB-12C-02



● CL-SB-12A-11
● CL-SB-12A-12



● CL-SB-12B-11
● CL-SB-12B-12



● CL-SB-12C-11
● CL-SB-12C-12



● CL-SB-22A-01
● CL-SB-22A-02



● CL-SB-22B-01
● CL-SB-22B-02



● CL-SB-22C-01
● CL-SB-22C-02



CL-SB
SLIDE SWITCHES

OUTLINE DIMESIONS

Unless otherwise specified, tolerance: ± 0.3 (Unit: mm)

● CL-SB-22A-11
● CL-SB-22A-12



● CL-SB-22B-11
● CL-SB-22B-12



● CL-SB-22C-11
● CL-SB-22C-12



● CL-SB-13A-01
● CL-SB-13A-02



● CL-SB-13B-01
● CL-SB-13B-02



● CL-SB-13C-01
● CL-SB-13C-02



● CL-SB-13A-11
● CL-SB-13A-12



● CL-SB-13B-11
● CL-SB-13B-12



● CL-SB-13C-11
● CL-SB-13C-12



CL-SB
SLIDE SWITCHES

● CL-SB-23A-01
● CL-SB-23A-02



● CL-SB-23B-01
● CL-SB-23B-02



● CL-SB-23C-01
● CL-SB-23C-02



● CL-SB-23A-11
● CL-SB-23A-12



● CL-SB-23B-11
● CL-SB-23B-12



● CL-SB-23C-11
● CL-SB-23C-12



CL-SB
SLIDE SWITCHES

■RECOMMENDED P.C.B. PAD OUTLINE DIMENSIONS

(Unit: mm)

● CL-SB-12A-□□



● CL-SB-12B-□□



● CL-SB-22A-□□



● CL-SB-22B-□□



● CL-SB-13A-□□



● CL-SB-13B-□□



● CL-SB-23A-□□



● CL-SB-23B-□□



● CL-SB-12C-□□



■SIZE OF P.C.B. PROCESSING

(Unit: mm)

● CL-SB-22C-□□



● CL-SB-13C-□□



● CL-SB-23C-□□



CL-SB
SLIDE SWITCHES

■ PACKAGING SPECIFICATIONS

<Bulk pack specifications>

- The smallest unit of bulk pack in plastic bag is 10 pcs. per pack.Orders will be accepted for unit of minimum 10 pcs., i.e., 10, 20, 30 pcs., etc.
- Boxing of bulk in a plastic bag is performed with 50 pcs. per box.

<Taping packaging specifications>

- Taping version is packaged in 500 pcs. per reel. Orders will be accepted for units of 500 pcs., i.e., 500, 1000, 1500, pcs., etc.
- Taping version is boxed with one reel (500 pcs.).

Maximum number of consecutive missing pieces=2
Leader length and reel dimension are shown in the diagrams below:

● Embossed tape dimensions



● Reel dimensions

(Unit: mm)

(Conforms to JIS C 0806-3)
(In accordance with EIAJ ET-7200A)



〈Tape dimensions〉

Unless otherwise specified, tolerance: ± 0.3 (Unit: mm)

● CL-SB-12A/12B-0 □ T

● CL-SB-22A/22B-0 □ T

(Conforms to JIS C 0806)





CL-SB
SLIDE SWITCHES

〈Tape dimensions〉

Unless otherwise specified, tolerance: ± 0.3 (Unit: mm)

● CL-SB-13A/13B-0 □ T

(Conforms to JIS C 0806)



● CL-SB-23A/23B-0 □ T

(Conforms to JIS C 0806)



● CL-SB-12A/12B-1 □ T

(Conforms to JIS C 0806)



● CL-SB-22A/22B-1 □ T

(Conforms to JIS C 0806)



● CL-SB-13A/13B-1 □ T

(Conforms to JIS C 0806)



● CL-SB-23A/23B-1 □ T

(Conforms to JIS C 0806)